

AP1010 Easy Plug & Play Tracker



Description

AP1010

AP1010 is an easy plug and track realtime tracking terminal with GPS/GLONASS and GSM connectivity, which is able to collect device coordinates and other useful data to transfer them via GSM network to server. This device is perfectly suitable for applications where location acquirement of remote objects is needed: fleet management, car rental companies, taxi companies, personal cars and so on.

Applications











Accessories/features





Internal backup battery

Trip detection

Overspeeding detection



Auto Geofencing

Detect car towing

Car theft prevention

Power saving



Features

- Plug and Track
- Small and easy to mount case directly to car OBDII connector
- Internal GSM antenna and Internal GPS/GLONASS antenna allow mount AP1010 much easier
- Real Time tracking

Smart data acquisition - based on time, distance, angle, ignition and I/O events allow to have precise online tracker

- Sending acquired data via GPRS (TCP/IP and UDP/IP protocols)
- Smart algorithm of GPRS connections for GPRS traffic saving
- Operating in roaming networks by preferred GSM providers list
- Events from I/O elements detection and sending via GPRS or SMS
- Scheduled 24 coordinates SMS sending when GPRS not available
- **5** geofence zones (rectangular or circle)
 - Auto Geofencing crested for car towing detection and car theft prevention
- Deep Sleep mode (less than 2 mA power consumption)
- FOTA (firmware updating via GPRS)
- 3 operational modes (Home, Roaming, Unknown) based on operator
- Integrated scenarios:
 - Over speeding to secure driver and prevent penalties
 - Trip start and end detection
- AP1010 supports a remote logs reading
 - AP1010 supports remote diagnostic logs functionality using GPRS. Possible issues resolving becomes faster. Manufacturer can read logs remotely using SMS/GPRS to diagnose the AP1010 and timely respond to the fault

Specification

GSM

- Quad-band 900/1800 MHz; 850/1900 MHz
- GPRS class 10 (up to 85,6 kbps)
- SMS (text/data)

GPS/GLONASS

- NMEA, GGA, GGL, GSA, GSV, RMC, VTG protocol compatible
- 32 channel GPS/GLONASS receiver
- Up to -161 dBm sensitivity

Interface

- I Digital Input Reserved for Ignition Status Monitoring (depends on vehicle type)
- Acceleromet
- Power supply (+10...+16) V DC
- Integrated back-up battery (optional)
- Internal High Gain GSM antenna
- Internal High Gain GPS/GLONASS antenna
- Dimensions: L(50,7mm)xW(49,6mm)xH(25mm)
- 2 Status LEDs
- Configuration and firmware upload (FOTA and via cable)



Accessories

USB to mini USB cable



AP1010 adapter for power connection not from OBDII connector



AP1010 adapter for power connection from cigarette lighter





 Suite 714 EGI City By The Sea, Maribago, Mactan, Lapu-lapu City, Cebu, Philippines 6015
: (6332) 495-2106, 233-0835
⊠ : apexsinc@mozcom.com
⊒ : www.apexvalue.com

Apexs, Inc. reserves a right to modify the functionality of the device without any prior notice. Document version 2.01 (2014/02/21)